

Safety Data Sheets

All Locations



Heidleberger

10/16/2020



Safety Data Sheet Index
Binder: Heidleberger - All Locations

Product Name	CAS Number	Manufacturer	Version Date	Page
Diesel fuel NO 2 - DIESEL FUEL No. 2		Chevron Products Company	06/04/2019	3

SAFETY DATA SHEET

1. Identification

Product identifier	Dykem® Metal Marking Texpen®/Dalo® (All Colors)
Other means of identification	
Part Number	Black (16030, 16033, 26033), Blue (16013, 26013), Green (16043, 26043), Orange (16103, 26103), Red (16020, 16023, 26023), White (16080, 16083, 16084, 16088, 26083, 26084), Yellow (16060, 16063, 16064, 16068, 26063, 26064)
Synonyms	Texpen - Fine, Medium and Broad * Dalo - Medium and Broad * FORMULA CODE(S): * J3070 (Black), J2143 (Blue) * Y916 (Green), A451M (Orange) * J3076 (Red), J1694 (White) * A419M (Yellow)
Recommended use	Solvent based marker
Recommended restrictions	None known.
Manufacturer/Importer/Supplier/Distributor information	
Manufacturer	
Company name	ITW Pro Brands
Address	805 E. Old 56 Highway Olathe, KS 66061
Country	(U.S.A.) Tel: +1 800-443-9536
In Case of Emergency	1-800-535-5053 (Infotrac)

2. Hazard(s) identification

Physical hazards	Flammable liquids	Category 3
Health hazards	Germ cell mutagenicity	Category 1B
	Carcinogenicity	Category 1B
	Specific target organ toxicity, repeated exposure	Category 1 (central nervous system)
	Aspiration hazard	Category 1
Environmental hazards	Not classified.	
OSHA defined hazards	Not classified.	

Label elements



Signal word	Danger
Hazard statement	Flammable liquid and vapor. May cause genetic defects. May cause cancer. Causes damage to organs (central nervous system) through prolonged or repeated exposure. May be fatal if swallowed and enters airways.
Precautionary statement	
Prevention	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe mist or vapor. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves/protective clothing/eye protection/face protection.
Response	If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If exposed or concerned: Get medical advice/attention. In case of fire: Use appropriate media to extinguish.
Storage	Store in a well-ventilated place. Keep cool. Store locked up.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC) None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Aromatic Solvent		64742-95-6	10 - 20
Kaolin		1332-58-7	10 - 20
Titanium Dioxide		13463-67-7	10 - 20
Hydrocarbon resin		68131-77-1	5 - 15
1,2,4-Trimethylbenzene		95-63-6	5 - 10
Resin		9003-55-8	5 - 10
Carbon Black		1333-86-4	1 - 5
Chlorinated Paraffin		63449-39-8	1 - 5
Mineral Spirits Regular Stoddard Solvent		8052-41-3	1 - 5
Silica, amorphous		7631-86-9	1 - 3
Aluminum Hydroxide		21645-51-2	0.1 - 1
Cumene		98-82-8	0.1 - 1
Light Mineral Spirits		64742-88-7	0.1 - 1
Xylene		1330-20-7	0.1 - 1

4. First-aid measures

Inhalation

Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact

Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical attention if irritation develops and persists.

Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Get medical attention if irritation develops and persists.

Ingestion

Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important symptoms/effects, acute and delayed

Aspiration may cause pulmonary edema and pneumonitis. Narcosis. Behavioral changes. Decrease in motor functions. Direct contact with eyes may cause temporary irritation. Prolonged exposure may cause chronic effects.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.

General information

Take off all contaminated clothing immediately. IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO₂).

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards

Flammable liquid and vapor.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not breathe mist or vapor. Avoid prolonged exposure. When using, do not eat, drink or smoke. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
Carbon Black (CAS 1333-86-4)	PEL	3.5 mg/m ³	
Cumene (CAS 98-82-8)	PEL	245 mg/m ³ 50 ppm	
Mineral Spirits Regular Stoddard Solvent (CAS 8052-41-3)	PEL	2900 mg/m ³ 500 ppm	
Titanium Dioxide (CAS 13463-67-7)	PEL	15 mg/m ³	Total dust.
Xylene (CAS 1330-20-7)	PEL	435 mg/m ³ 100 ppm	

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
Carbon Black (CAS 1333-86-4)	TWA	3 mg/m ³	Inhalable fraction.
Cumene (CAS 98-82-8)	TWA	50 ppm	
Kaolin (CAS 1332-58-7)	TWA	2 mg/m ³	Respirable fraction.

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
Mineral Spirits Regular Stoddard Solvent (CAS 8052-41-3)	TWA	100 ppm	
Titanium Dioxide (CAS 13463-67-7)	TWA	10 mg/m3	
Xylene (CAS 1330-20-7)	STEL	150 ppm	
	TWA	100 ppm	

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
1,2,4-Trimethylbenzene (CAS 95-63-6)	TWA	125 mg/m3	
		25 ppm	
Carbon Black (CAS 1333-86-4)	TWA	0.1 mg/m3	
Cumene (CAS 98-82-8)	TWA	245 mg/m3	
		50 ppm	
Kaolin (CAS 1332-58-7)	TWA	5 mg/m3	Respirable.
		10 mg/m3	Total
Mineral Spirits Regular Stoddard Solvent (CAS 8052-41-3)	Ceiling	1800 mg/m3	
	TWA	350 mg/m3	
Silica, amorphous (CAS 7631-86-9)	TWA	6 mg/m3	
Xylene (CAS 1330-20-7)	STEL	655 mg/m3	
	TWA	150 ppm 435 mg/m3 100 ppm	

Biological limit values

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
Xylene (CAS 1330-20-7)	1.5 g/g	Methylhippuric acids	Creatinine in urine	*

* - For sampling details, please see the source document.

Exposure guidelines

US - California OELs: Skin designation

Cumene (CAS 98-82-8) Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

Cumene (CAS 98-82-8) Skin designation applies.

US - Tennessee OELs: Skin designation

Cumene (CAS 98-82-8) Can be absorbed through the skin.

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

Cumene (CAS 98-82-8) Can be absorbed through the skin.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Cumene (CAS 98-82-8) Can be absorbed through the skin.

Appropriate engineering controls

Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection	Use a positive-pressure air-supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air-purifying respirators may not provide adequate protection.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state	Liquid.
Form	Liquid.
Color	Various.
Odor	Aromatic.
Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	318 - 338 °F (158.89 - 170 °C)
Flash point	108.0 °F (42.2 °C) Tag Closed Cup
Evaporation rate	< 1 (BuAc = 1)
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	1.9 %
Flammability limit - upper (%)	12.3 %
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	> 1 (air = 1)
Relative density	> 1 @70°F
Solubility(ies)	
Solubility (water)	Slightly soluble.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.
VOC	J2143 Blue: 30.78%, 399 g/L, A451M Orange: 28.97%, 352 g/L; J1694 White: 21.49%, 321 g/L J3070 Black: 30.97%, 382 g/L; Y916 Green: 30.9%, 375 g/L; J3076 Red: 35.58%, 430 g/L; A419M Yellow: 28.73%, 351 g/L;

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.
Hazardous decomposition products Carbon oxides.

11. Toxicological information

Information on likely routes of exposure

Inhalation May cause damage to organs through prolonged or repeated exposure by inhalation.
Skin contact No adverse effects due to skin contact are expected.
Eye contact Direct contact with eyes may cause temporary irritation.
Ingestion Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

Symptoms related to the physical, chemical and toxicological characteristics Aspiration may cause pulmonary edema and pneumonitis. Narcosis. Behavioral changes. Decrease in motor functions.

Information on toxicological effects

Acute toxicity May be fatal if swallowed and enters airways.

Components	Species	Test Results
1,2,4-Trimethylbenzene (CAS 95-63-6)		
Acute		
Dermal		
LD50	Rabbit	> 3160 mg/kg
Oral		
LD50	Rat	3280 mg/kg
Aluminum Hydroxide (CAS 21645-51-2)		
Acute		
Oral		
LD50	Rat	> 2000 mg/kg
Aromatic Solvent (CAS 64742-95-6)		
Acute		
Dermal		
LD50	Rabbit	> 1900 mg/kg, 24 Hours
Inhalation		
<i>Vapor</i>		
LC50	Rat	> 4.96 mg/l, 4 Hours
Oral		
LD50	Rat	4820 mg/kg
CALCIUM ROSINATE (CAS 9007-13-0)		
Acute		
Dermal		
LD50	Rat	> 2000 mg/kg, 24 Hours
Oral		
LD50	Rat	> 1000 mg/kg
Cumene (CAS 98-82-8)		
Acute		
Dermal		
LD50	Rabbit	> 3160 mg/kg, 24 Hours
Light Mineral Spirits (CAS 64742-88-7)		
Acute		
Dermal		
LD50	Rabbit	> 2000 mg/kg

Components	Species	Test Results
Inhalation		
<i>Vapor</i>		
LC50	Rat	> 4.5 mg/l, 4 Hours
Silica, amorphous (CAS 7631-86-9)		
Acute		
Dermal		
LD50	Rabbit	> 2000 mg/kg, 24 Hours
Oral		
LD50	Rat	> 3300 mg/kg
Titanium Dioxide (CAS 13463-67-7)		
Acute		
Inhalation		
LC50	Rat	> 2.28 mg/l, 4 Hours
Oral		
LD50	Rat	> 2000 mg/kg
Xylene (CAS 1330-20-7)		
Acute		
Oral		
LD50	Rat	3523 mg/kg
Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation.	
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.	
Respiratory or skin sensitization		
Respiratory sensitization	Not a respiratory sensitizer.	
Skin sensitization	This product is not expected to cause skin sensitization.	
Germ cell mutagenicity	May cause genetic defects.	
Carcinogenicity	May cause cancer.	
ACGIH Carcinogens		
Carbon Black (CAS 1333-86-4)	A3 Confirmed animal carcinogen with unknown relevance to humans.	
Kaolin (CAS 1332-58-7)	A4 Not classifiable as a human carcinogen.	
Titanium Dioxide (CAS 13463-67-7)	A4 Not classifiable as a human carcinogen.	
Xylene (CAS 1330-20-7)	A4 Not classifiable as a human carcinogen.	
IARC Monographs. Overall Evaluation of Carcinogenicity		
Carbon Black (CAS 1333-86-4)	2B Possibly carcinogenic to humans.	
Cumene (CAS 98-82-8)	2B Possibly carcinogenic to humans.	
Resin (CAS 9003-55-8)	3 Not classifiable as to carcinogenicity to humans.	
Silica, amorphous (CAS 7631-86-9)	3 Not classifiable as to carcinogenicity to humans.	
Titanium Dioxide (CAS 13463-67-7)	2B Possibly carcinogenic to humans.	
Xylene (CAS 1330-20-7)	3 Not classifiable as to carcinogenicity to humans.	
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)		
Not regulated.		
US. National Toxicology Program (NTP) Report on Carcinogens		
Cumene (CAS 98-82-8)	Reasonably Anticipated to be a Human Carcinogen.	
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.	
Specific target organ toxicity - single exposure	Not classified.	
Specific target organ toxicity - repeated exposure	Causes damage to organs (central nervous system) through prolonged or repeated exposure.	
Aspiration hazard	May be fatal if swallowed and enters airways.	
Chronic effects	Causes damage to organs through prolonged or repeated exposure. Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.	
Further information	Symptoms may be delayed.	

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components	Species	Test Results
1,2,4-Trimethylbenzene (CAS 95-63-6)		
Aquatic		
Fish	LC50	Fathead minnow (<i>Pimephales promelas</i>) 7.19 - 8.28 mg/l, 96 hours
Chlorinated Paraffin (CAS 63449-39-8)		
Aquatic		
Fish	LC50	Bluegill (<i>Lepomis macrochirus</i>) > 0.1 mg/l, 96 hours
Cumene (CAS 98-82-8)		
Aquatic		
Crustacea	EC50	Brine shrimp (<i>Artemia</i> sp.) 3.55 - 11.29 mg/l, 48 hours
Fish	LC50	Rainbow trout, donaldson trout (<i>Oncorhynchus mykiss</i>) 2.7 mg/l, 96 hours
Titanium Dioxide (CAS 13463-67-7)		
Aquatic		
Crustacea	EC50	Water flea (<i>Daphnia magna</i>) > 1000 mg/l, 48 hours
Fish	LC50	Mummichog (<i>Fundulus heteroclitus</i>) > 1000 mg/l, 96 hours
Xylene (CAS 1330-20-7)		
Aquatic		
Fish	LC50	Bluegill (<i>Lepomis macrochirus</i>) 7.711 - 9.591 mg/l, 96 hours

Persistence and degradability No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

Cumene	3.66
Mineral Spirits Regular Stoddard Solvent	3.16 - 7.15
Xylene	3.12 - 3.2

Mobility in soil No data available.

Other adverse effects None known.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues / unused products Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

UN number	UN1263
UN proper shipping name	Paint
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Label(s)	3
Packing group	III
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	B1, B52, IB3, T2, TP1, TP29
Packaging exceptions	150

Packaging non bulk 173
Packaging bulk 242

IATA

UN number UN1263
UN proper shipping name Paint
Transport hazard class(es)
Class 3
Subsidiary risk -
Packing group III
Environmental hazards No.
ERG Code 3L
Special precautions for user Read safety instructions, SDS and emergency procedures before handling.
Other information
Passenger and cargo aircraft Allowed with restrictions.
Cargo aircraft only Allowed with restrictions.

IMDG

UN number UN1263
UN proper shipping name PAINT
Transport hazard class(es)
Class 3
Subsidiary risk -
Packing group III
Environmental hazards
Marine pollutant No.
EmS F-E, S-E
Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not established.

DOT



IATA; IMDG



15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

TSCA Chemical Action Plans, Chemicals of Concern

Chlorinated Paraffin (CAS 63449-39-8)

Short-Chain Chlorinated Paraffins (SCCPs) and Other Chlorinated Paraffins Action Plan

CERCLA Hazardous Substance List (40 CFR 302.4)

Cumene (CAS 98-82-8)

Listed.

Xylene (CAS 1330-20-7)

Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)**SARA 302 Extremely hazardous substance**

Not listed.

Classified hazard categories

Flammable (gases, aerosols, liquids, or solids)
 Germ cell mutagenicity
 Carcinogenicity
 Specific target organ toxicity (single or repeated exposure)
 Aspiration hazard

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
1,2,4-TRIMETHYLBENZENE	95-63-6	5 - 10

Other federal regulations**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Cumene (CAS 98-82-8)

Xylene (CAS 1330-20-7)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.

US state regulations**US. New Jersey Worker and Community Right-to-Know Act**

1,2,4-Trimethylbenzene (CAS 95-63-6)

CALCIUM ROSINATE (CAS 9007-13-0)

Carbon Black (CAS 1333-86-4)

Cumene (CAS 98-82-8)

Kaolin (CAS 1332-58-7)

Mineral Spirits Regular Stoddard Solvent (CAS 8052-41-3)

Titanium Dioxide (CAS 13463-67-7)

Xylene (CAS 1330-20-7)

California Proposition 65**WARNING:** WARNING: This product contains a chemical known to the State of California to cause cancer.**California Proposition 65 - CRT: Listed date/Carcinogenic substance**

Cumene (CAS 98-82-8)

Listed: April 6, 2010

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

1,2,4-Trimethylbenzene (CAS 95-63-6)

Aromatic Solvent (CAS 64742-95-6)

Carbon Black (CAS 1333-86-4)

Chlorinated Paraffin (CAS 63449-39-8)

Cumene (CAS 98-82-8)

Mineral Spirits Regular Stoddard Solvent (CAS 8052-41-3)

Titanium Dioxide (CAS 13463-67-7)

Xylene (CAS 1330-20-7)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes

Country(s) or region	Inventory name	On inventory (yes/no)*
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Toxic Chemical Substances (TCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 04-16-2018

Version # 01

Disclaimer ITW Pro Brands cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Revision information Product and Company Identification: Alternate Trade Names
Hazard(s) identification: Response
Composition / Information on Ingredients: Ingredients
Physical & Chemical Properties: Multiple Properties
Regulatory information: California Proposition 65